



GP 12170

12V 17.0Ah

GP 12170 is a general purpose battery with 3-5 years in standby service or more than 260 cycles at 100% discharge in cycle service. As with all CSB batteries, all are rechargeable, highly efficient, leak proof and maintenance free.



Specification




Cells Per Unit	6
Voltage Per Unit	12
Capacity	17Ah @ 20hr-rate to 1.75V per cell @25 °C (77°F)
Weight	Approx. 5.85kg(12.9 lbs)
Maximum Discharge Current	230A(5sec)
Internal Resistance	Approx. 14.5mΩ
Operating Temperature Range	Discharge: -20°C~50°C (-4°F~122°F) Charge: 0°C~40°C (32°F~104°F) Storage: -20°C~40°C (-4°F~104°F)
Nominal Operating Temperature Range	25°C±3°C (77°F±5°F)
Float Charging Voltage	13.5 to 13.8 VDC/unit Average at 25°C (77°F)
Recommended Maximum Charging Current Limit	5.1A
Equalization and Cycle Service	14.4 to 15.0 VDC/unit Average at 25°C (77°F)
Self Discharge	CSB Batteries can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	Bolt & Nut
Container Material	-ABS (UL94-HB)*Flammability resistance of UL94-V0 can be available upon request.



CSB-manufactured batteries are UL-recognized components under UL924 and UL1989. CSB is also certified by ISO 9001 and ISO 14001.

Dimensions

unit: (MM)



Constant Current Discharge Characteristics Unit:A (25°C, 77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	80.17	50.92	38.50	23.42	13.83	8.03	5.72	4.44	3.63	2.37	1.93	1.00
1.67V	71.25	47.48	36.75	23.07	13.77	8.03	5.71	4.43	3.62	2.36	1.90	0.96
1.70V	67.42	46.00	36.00	22.92	13.75	8.03	5.70	4.43	3.61	2.35	1.89	0.94
1.75V	60.96	43.09	34.34	22.34	13.54	7.96	5.66	4.41	3.60	2.33	1.86	0.91
1.80V	54.50	40.17	32.67	21.75	13.33	7.88	5.61	4.38	3.58	2.30	1.83	0.88
1.85V	48.04	37.26	31.01	21.17	13.12	7.81	5.57	4.36	3.57	2.28	1.80	0.85

Constant Power Discharge Characteristics Unit:W (25°C, 77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	890.22	582.81	448.53	281.00	166.00	96.40	68.60	53.30	43.60	28.40	23.10	12.00
1.67V	790.32	543.88	428.72	276.80	165.30	96.33	68.46	53.23	43.39	28.26	22.82	11.51
1.70V	748.14	526.70	419.40	275.00	165.00	96.30	68.40	53.20	43.30	28.20	22.70	11.30
1.75V	677.10	493.50	399.60	268.00	162.50	95.45	67.85	52.90	43.15	27.90	22.35	10.90
1.80V	604.95	460.29	380.96	261.00	160.00	94.60	67.30	52.60	43.00	27.60	22.00	10.50
1.85V	532.80	427.09	361.15	254.00	157.50	93.75	66.75	52.30	42.85	27.30	21.65	10.10


• All mentioned values are average values.

GP 12170


12V 17.0Ah




Trickle (or Float) Service Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use




Cycle Service Life



Battery Voltage and Charge Time for Cycle Use



Terminal Voltage (V) and Discharge Time (25°C 77°F)



Charging Procedures

Application	Charge Voltage (V/Cell)			Max. Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C (77°F)	2.45	2.40~2.50	0.3C
Standby	25°C (77°F)	2.275	2.25~2.30	

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.55	1.30
Discharge Current (A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C